



温州市华侨包装机械厂
WENZHOU HUAQIAO PACKING MACHINE FACTORY

内销部 Domestic Sales Department
地址：浙江省温州市空港新区港富路15号
ADD: NO.15 Gangfu Road, Konggang
New Area, Wenzhou, Zhejiang.
电话(TEL): 0577-88633888 88631988
传真(FAX): 0577-88628808

外贸部 International Department
电话(TEL): +86-577-88998813
传真(FAX): +86-577-88996613
<http://www.huaqiaopm.com>
E-mail: huaqiaopm@huaqiaopm.com

上海工厂 Shanghai Factory
地址：上海市嘉定区黄渡镇春浓路732号
ADD: NO.732 Chunnong Road, Huangdu Town
Jiading Area Shanghai
电话(TEL): 021-69596266 69596268
传真(FAX): 021-69596267
<http://www.afanlao.com>
E-mail: afanlao@afanlao.com

HAOWU

封口机系列





温州市华侨包装机械厂成立于一九八七年，专业生产“捆霸牌”包装机械和食品机械等产品，公司技术力量雄厚、设备齐全、具有开发、研制、生产、销售及售后服务的完整体系。本公司主要产品有：塑料带捆扎机、自动封箱机、超声波自动封口机、真空包装机、墨轮印字封口机、多功能薄膜封口机、盒杯封盖机、打码机、移印机、吸塑包装机、贴体包装机、液体、颗粒、粉剂自动包装机、电磁感应封盖机。自动贴标机和流水线，设计制作等。我厂产品畅销全国二十九个省、市、自治区。并出口东南亚、中东、欧美等国家和地区。其中半自动捆包机已连年创中国销量之最。被中国产品质量协会推荐为“质量信得过产品”。企业通过了ISO9001国际质量体系认证。部分产品已通过欧盟的CE认证，并且是美国中央采购中心采购单位，我们始终本着“为客户创造价值”的核心价值观，不新开拓创新，奋发进取。力争为每一位客户提供品质卓越的产品及完美周到的售前售后服务。我们致力于新产品开发、质量的提高及今后服务的完善，“坚持不懈地力求完美”是我们的宗旨，针对国内外市场的需求，我们不断地开发质优价宜的各类包装机械，广泛应用于各行业。“只有客户的成功、才有华侨的发展”。华侨企业竭诚与国内外各界客商携手合作，共同迈向成功！

Wenzhou Huaqiao Packing Machine Factory, the owner of KUNBA brand, established in 1987 is a professional manufacturer specialized in vacuum packing machine, sealing machine, carton sealer, date printing machine, strapping machine, cup sealer, shrink tunnel, induction foil sealer, liquid/semi-liquid filling machine. We are located near the wenzhou airport with convenient transportation. All of our products comply with international quality standards and are greatly appreciated in a variety of different markets throughout the world.



- ◆ Devote to Packing Machine since 1987.
- ◆ 90000 square meters , 150 employees.
- ◆ Over 10 million dollars annual sales, 60% export to worldwide.
- ◆ well-equipped facilities and excellent quality control
- ◆ ISO9001:2008 CE certificate approved.
- ◆ OEM and customized -design service supplied.

WORKSHOP OVERVIEW

车间概览

一流的技术设备，一流的生产配置，时现代企业必不可少的硬件，也是制造优质产品的保证。我们公司持续购进先进的生产设备，引进新材料、新工艺，使产品大众化、品质化。

技术专家直接参与技术指导及生产，保证了产品的稳定性和可靠性。员工与日俱增的精品意识和源源不断的工业精品另世界包装业日新月异。

我们以客户为导向，以研究和制造客户需要的、满意的产品为己任。我们凭借其技术的优势和先进的生产工艺、产品开发的能力，把技术研究水平和生产工艺发挥的淋漓尽致。从而让客户得到真正的认同和赞赏。



加工设备 PROCESSING EQUIPMENT



Manual Sealer/Pedal Sealer

手压/脚踏封口机



手压封口机（塑壳、铝壳）
Manual Sealer(plastic、aluminum)

PFS100-400

技术参数/Technology Parameters				
型号/Model	PFS100	PFS200	PFS300	PFS400
电源电压/Power Supply	AC110-220V/60-50Hz	AC110-220V/60-50Hz	AC110-220V/60-50Hz	AC110-220V/60-50Hz
总功率/Power Consumption	250W	300W	450W	600W
最大封口尺寸/Max Sealing Size	150mm	200mm	300mm	400mm
外包装尺寸/Shipment Dimension	72X220X10mm	80X320X150mm	80X450X180mm	85X550X180mm
毛重/Gross Weight	1.9kg	3.0kg	4.5kg	5.5kg

脚踏封口机（落地式）
Pedal Sealer (ground)

PFS350-800JT

技术参数/Technology Parameters				
型号/Model	PFS350JT	PFS450JT	PFS600JT	PFS800JT
电源电压/Power Supply	AC110-220V/60-50HZ	AC110-220V/60-50HZ	AC110-220V/60-50HZ	AC110-220V/60-50HZ
总功率/Power Consumption	1200W	1250W	1500W	1800W
最大封口尺寸/Max Sealing Size	350mm	450mm	600mm	800m
外包装尺寸/Shipment Dimension	880X550x250mm	880X550X250mm	880X550X250mm	920X550X250mm
毛重/Gross Weight	19kg	21kg	24.5kg	26kg

脚踏封口机（带打码）
Pedal Sealer (with Printer)

PFS350-800JT

技术参数/Technology Parameters				
型号/Model	PFS350JT	PFS450JT	PFS600JT	PFS800JT
电源电压/Power Supply	AC110-220V/60-50Hz	AC110-220V/60-50Hz	AC110-220V/60-50Hz	AC110-220V/60-50Hz
总功率/Power Consumption	1500W	1700W	1900W	2100W
最大封口尺寸/Max Sealing Size	350mm	450mm	600mm	800mm
外包装尺寸/Shipment Dimension	880X550X250mm	880X550X250mm	880X550X250mm	920X550X250mm
毛重/Gross Weight	21kg	23kg	27kg	28kg

MULTI-FUNCTIONAL FILM SEALER

多功能薄膜封口机

KUNBA牌系列薄膜封口机适用于各种塑料薄膜的封口与制袋，广泛应用于食品、医药、化工、土特产品、电子元件等行业，它是工厂、商店等部门使用的最佳封口设备

PATENT NUMBER: ZL02219651.X

中国专利号: ZL02219651.X

- Adjustable temperature and peed
- Coding fan protect film from wrinkle
- Durable heater and motor
- Work smoothly without wear and tear
- Enboss number and letter

卧式薄膜封口机
Continuous sealer (Horizontal)

SF-150W



技术参数/Technology Parameters	
型号/Model	SF-150W
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	60W
电热功率/Heating Power	280W×2
封口速度/Sealing Speed	0-16m/min (米/分)
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	860×410×375mm
净重/毛重/N.W&G.W	20.5kg/23.5kg

立式薄膜封口机
Continuous sealer (Vertial)

SF-150LW



技术参数/Technology Parameters	
型号/Model	SF-150LW
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	60W
电热功率/Heating Power	280W×2
封口速度/Sealing Speed	0-16m/min (米/分)
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	860×410×375mm
净重/毛重/N.W&G.W	23.5kg/26.5kg

落地式薄膜封口机
Continuous sealer (Ground)

SF-150LD



技术参数/Technology Parameters	
型号/Model	SF-150LD
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	60W
电热功率/Heating Power	280W×2
封口速度/Sealing Speed	0-16m/min (米/分)
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	965×430×445mm
净重/毛重/N.W&G.W	29.5kg/32.5kg

SOLID INK CONTINUOUS SEALER

墨轮印字薄膜封口机

PATENT NUMBER: ZL02219651.X

中国专利号: ZL02219651.X

- Adjustable printing position tmperature and speed
- Coding fan protect film from wrinkle
- Durable heater and motor
- Work smoothly without wear and tear
- Print 3 lines with ink
- Vertical and horizontal double-use

卧式墨轮印字封口机
Solid continuous sealer(Horizontal)

FRM-980W



技术参数/Technology Parameters	
型号/Model	FRM-980W
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	80W
封口电热功率/Heating Power	280W×2
印字电热功率/Printing Power	60W×2
封口速度/Sealing Speed	0-16m/min (米/分)
印字类别/Printing Material	固体墨轮/solid-ink
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	965×430×380mm
净重/毛重/N.W&G.W	25.5kg/28.5kg

立式墨轮印字封口机
Solid continuous sealer(Vertical)

FRM-980LW



技术参数/Technology Parameters	
型号/Model	FRM-980LW
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	80W
封口电热功率/Heating Power	280W×2
印字电热功率/Printing Power	60W×2
封口速度/Sealing Speed	0-16m/min (米/分)
印字类别/Printing Material	固体墨轮/solid-ink
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	965×430×380mm
净重/毛重/N.W&G.W	28.7kg/31.7kg

落地式墨轮印字封口机
Solid continuous sealer(Ground)

FRM-980LD



技术参数/Technology Parameters	
型号/Model	FRM-980LD
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	80W
封口电热功率/Heating Power	280W×2
印字电热功率/Printing Power	60W×2
封口速度/Sealing Speed	0-16m/min (米/分)
印字类别/Printing Material	固体墨轮/solid-ink
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	965×430×445mm
净重/毛重/N.W&G.W	35.5kg/38.5kg

SOLID INK CONTINUOUS SEALER

墨轮印字薄膜封口机

卧式色带打码印字薄膜封口机
Ribbon code printing film sealing machine (Horizontal)

SF-150SD



技术参数/Technology Parameters	
型号/Model	SF-150SD
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	60W+15W
封口电热功率/Heating Power	280W×2
封口速度/Sealing Speed	0-16m/min (米/分)
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	980×470×550mm
净重/毛重/N.W&G.W	30kg/47.8kg

EUROPEAN STANDARD PROTECTIVE TYPE
CONTINUOUS BAG SEALER

连续式封口机

卧式薄膜封口机（防护型）
Horizontal film sealing machine (protective type)

SF-150WF



技术参数/Technology Parameters	
型号/Model	SF-150WF
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	60W
电热功率/Heating Power	280W×2
封口速度/Sealing Speed	0-16m/min (米/分)
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	860×410×375mm
净重/毛重/N.W&G.W	21.5kg/24.5kg

豪华型卧式墨轮印字封口机
Solid-inker printer film sealer(Horizontal)

FRD-980AI



技术参数/Technology Parameters	
型号/Model	FRD-980AI
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	80W
封口电热功率/Heating Power	280W×2
印字电热功率/Printing Power	60W×2
封口速度/Sealing Speed	0-16m/min (米/分)
印字类别/Printing Material	固体墨轮/solid-ink
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	965×430×380mm
净重/毛重/N.W&G.W	27.15kg/30.3kg

卧式墨轮印字封口机（防护型）
Horizontal ink printing sealing machine (protective type)

FRM-980WF



技术参数/Technology Parameters	
型号/Model	FRM-980WF
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	80W
封口电热功率/Heating Power	280W×2
印字电热功率/Printing Power	60W×2
封口速度/Sealing Speed	0-16m/min (米/分)
印字类别/Printing Material	固体墨轮/solid-ink
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	965×430×380mm
净重/毛重/N.W&G.W	26.5kg/29.5kg

充氮气型卧式薄膜封口机
Nitrogen flushing continous sealing machine

FRQM-980CD



技术参数/Technology Parameters	
型号/Model	FRQM-980CD
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	80W
电热功率/Heating Power	280W×2
封口速度/Sealing Speed	0-16m/min (米/分)
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	965×430×380mm
净重/毛重/N.W&G.W	26.0kg/29.0kg

卧式墨轮印字封口机（加宽防护型）
Horizontal ink printing sealing machine (wide conveyor protective type)

FRM-980WK



技术参数/Technology Parameters	
型号/Model	FRM-980WK
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	80W
封口电热功率/Heating Power	280W×2
印字电热功率/Printing Power	60W×2
封口速度/Sealing Speed	0-16m/min (米/分)
印字类别/Printing Material	固体墨轮/solid-ink
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	1060×610×420mm
净重/毛重/N.W&G.W	36kg/45kg

SOLID INK CONTINUOUS SEALER

墨轮印字（充气）封口机

落地式充气薄膜封口机
Air-filling continuous sealer

FRQM-980C



技术参数/Technology Parameters	
型号/Model	FRQM-980C
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	80W
气泵功率/Airpump Power	200W
封口电热功率/Heating Power	28W×2
封口速度/Sealing Speed	0-16m/min（米/分）
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	1030×590×880mm
净重/毛重/N.W&G.W	41kg/48kg

落地式充气墨轮印字封口机
Air-filling and ink printing continuous sealing machine

FRSC-101011



技术参数/Technology Parameters	
型号/Model	FRSC-101011
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	80W
气泵功率/Airpump Power	200W
封口速度/Sealing Speed	0-16m/min（米/分）
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤5kg
外包装尺寸/Shipment Dimension	1140×595×885mm
净重/毛重/N.W&G.W	46kg/53kg

多功能连续式真空抽气/充气包装机
Continuous-vacuum pumping and air filling sealing machine

FRSZ-12801



技术参数/Technology Parameters	
型号/Model	FRSZ-12801
电源电压/Power Supply	AC220/50Hz 110V/60Hz
电机功率/Power Consumption	80W
气泵功率/Airpump Power	200W
封口速度/Sealing Speed	0-16m/min（米/分）
封口宽度/Sealing Width	10mm
温控范围/Temperature Range	0-300℃
输送总承载/Conveyor Loading	≤3kg
外包装尺寸/Shipment Dimension	1140×600×890mm
净重/毛重/N.W&G.W	78kg

MLTI-FUNCTIONAL FILM SEALER

多功能薄膜封口机

气压大袋封口机
Air pressure sealing machine for big plastic bag

QF-700L



技术参数/Technology Parameters	
型号/Model	QF-700L
电源电压/Power Supply	AC220-240/50Hz
总功率/Power Consumption	500W
封口速度/Sealing Speed	0-13M/min（米/分）可调
封口宽度/Sealing Width	8-10mm
温控范围/Temperature Range	0-300℃
袋长范围/Bag Length Range	50-700mm可调
输送总承载/Conveyor Loading	15kg
外包装尺寸/Shipment Dimension	720×560×1340mm
毛重/Gross Weight	130kg
薄膜厚度/Sealing Film Thickness	0.1-0.8mm

多功能卧式封口机
Multi-functional film sealer(HORIZONTAL)

CBS-1100H



技术参数/Technology Parameters	
型号/Model	CBS-1100H
电源电压/Power Supply	220V single phase 50/60Hz
总功率/Power Consumption	750W
封口速度/Sealing Speed	0-12m/min
封口宽度/Sealing Width	5-10mm
薄膜厚度/Sealing Film Thickness	0.02-0.8mm
温控范围/Temperature Range	0-300℃
印字个数/Print Capacity	≤39
输送总承载/Conveyor Loading	20kg
外包装尺寸/Shipment Dimension	1100×610×1030mm
毛重/Gross Weight	122kg

多功能立式封口机
Multi-functional film sealer(Vertical)

CBS-1100V



技术参数/Technology Parameters	
型号/Model	CBS-1100V
电源电压/Power Supply	220V single phase 50/60Hz
总功率/Power Consumption	750W
封口速度/Sealing Speed	0-12m/min
封口宽度/Sealing Width	5-10mm
薄膜厚度/Sealing Film Thickness	0.02-0.8mm
温控范围/Temperature Range	0-300℃
印字个数/Print Capacity	≤39
输送总承载/Conveyor Loading	20kg
外包装尺寸/Shipment Dimension	1100×610×1030mm
毛重/Gross Weight	122kg
可调高度/Adjustable Height	180-600mm

COLOURED-TAPE PRINTER

HP系列色带打码机

捆霸牌系列打码机广泛适用于食品、医药等行业，具有印刷精美，字迹牢固，无污染，换字方便等优点，能完美印刷各种包装材料，如：PT、PE、OPP、铝箔、纸等。

手压色带打码机（电脑版）
Hand ribbon printer(Digital version)

HP-241S

- Special design economize ribbons
- Stable footing
- Clear printing
- No hazard
- 3 lines of letter an number



技术参数/Technology Parameters	
型号/Model	HP-241S
电源电压/Power Supply	AC110-220V/60-50Hz
总功率/Power Consumption	100W
印字行数/Heating Power	1-3行 (line)
字粒尺寸/Size of letter&number	2×3×15/2×4×15
速度/Sealing Width	20-120pcs/min
外包装尺寸/Shipment Dimension	240×240×140mm
净重/毛重/N.W&G.W	5.0KG/5.6KG

电动色带打码机（电脑版）
Electrical ribbon printer(Digital version)

HP-23S



技术参数/Technology Parameters	
型号/Model	HP-23S
电源电压/Power Supply	AC110-220V/60-50Hz
总功率/Power Consumption	120W
印字行数/Heating Power	1-3行 (line)
字粒尺寸/Size of letter&number	2×3×15/2×4×15
速度/Sealing Width	20-120pcs/min
外包装尺寸/Shipment Dimension	295×285×350mm
净重/毛重/N.W&G.W	8.5kg/9.3kg



励磁电机 + 高效涡轮蜗杆减速箱



斜齿轮 转动平稳 噪声小 承载力强 啮合性好

INDUCTION SEALING MACHINE

电磁感应封口机

手持式电磁感应封口机
Portable aluminum foil induction sealing machine

GLF-500



技术参数/Technology Parameters	
型号/Model	GLF-500
电源电压/Power Supply	AC220-240V/50Hz
总功率/Power Consumption	≤500W
工作效率/Capacity	12-30pcs/min
封口直径/Sealing Diameter	φ20-φ100mm
容器高度/Sealing Height	无限高度Height unlimited
外包装尺寸/Shipment Dimension	340×290×150mm
毛重/Gross Weight	5kg

连续式电磁感应封口机
Continuous induction sealing machine

GLF-900



技术参数/Technology Parameters	
型号/Model	GLF-900
电源电压/Power Supply	AC220-240V/50Hz
总功率/Power Consumption	≤500W
工作效率/Capacity	0-10m/s
封口直径/Sealing Diameter	φ20-φ50mm
容器高度/Sealing Height	40-200mm
外包装尺寸/Shipment Dimension	925×540×440mm
毛重/Gross Weight	47kg

大型连续式电磁感应封口机
Continuous induction alummium

FNJ-1900



技术参数/Technology Parameters	
型号/Model	FNJ-1900
电源电压/Power Supply	AC220V50/60Hz
总功率/Power Consumption	2000W
封口直径/Sealing Diameter	φ50-φ120mm
封口速度/Sealing Speed	1-100瓶/分钟0-100bottles per minute
瓶子高度/Height Of Sealing Bottle	30-350mm
机器尺寸/Machine Size	1440×500×1350mm
毛重/Gross Weight	96kg

备注

**坚持不懈
力求完美**
CONSTANTLY STRIVE
TO PERFECT
只有客户的成功、才有华侨的发展

备注